



TECHNICAL DATA SHEET

369 UAE – URETHANE ADDITIVE FOR ENAMEL

Page 1/1
Revised: April 2008

DESCRIPTION	369 UAE is a high performance aliphatic isocyanate resin solution used as an additive to both 363 AUTOMOTIVE ENAMEL and 304 EQUIPMENT ENAMEL to improve drying, hardness, chemical resistance, gloss and durability.
PRODUCT #	<ul style="list-style-type: none">• 369 - 9201
MIXING	<ul style="list-style-type: none">• Add 500 mls of 369 UAE to 4 Litres of 363 AUTOMOTIVE ENAMEL.• Add 250 mls of 369 UAE to 4 Litres of 304 EQUIPMENT ENAMEL.• Mix in well• Allow to stand 10 minutes before use.
PACK SIZES	<ul style="list-style-type: none">• 500mL

PRECAUTIONS

Addition of 369 UAE to either enamel converts that material into a 2 Pack urethane enamel containing volatile organic isocyanate. All precautions relative to the handling, mixing and spraying of 2 Pack urethane enamels must be adhered to.

369 UAE must be kept firmly sealed as it deteriorates rapidly on exposure to air. If using only portion, reseal container thoroughly after use and plan to use the remainder as soon as practicable.

HEALTH AND SAFETY

Breathing fumes and spray mist can cause sensitisation and asthma like reaction. Persons suffering from chronic respiratory problems should not use this product. All mixing and handling of 369 UAE and paint containing it must be carried out under conditions that prevent skin contact and inhalation of vapour. Wear impervious gloves in a ventilated booth fitted with an effective exhaust system. Wear a positive pressure air supplied full face respirator (complying with Australian Standard 1716) and gloves while spraying and until all spray mist has been effectively dispersed. 369 UAE also contains volatile flammable solvents. Keep away from all sources of heat and open flames. Do NOT smoke whilst handling.

FIRST AID

Eyes	If splashed in eyes, irrigate with copious amounts of clean water for 15 minutes. Seek medical aid if irritation persists.
Skin	If splashed on skin, wash affected area thoroughly with soap and water. If irritation persists seek medical aid. Remove all contaminated clothing and launder before re-use.
Inhalation	If affected by exposure to vapours, remove from area, keep at rest and seek medical aid if symptoms persist.
Ingestion	If swallowed, give glass of water to drink and seek medical assistance. DO NOT induce vomiting.

Consult separate Material Safety Data Sheet for more detailed Health and Safety information.