

PH-2400

PARAGLAZE CT BASECOAT ACTIVATOR

PRODUCT DESCRIPTION

Paraglaze CT Basecoat Activator is added to Paraglaze Basecoat to provide a tougher, more durable paint system with improved stone chip resistance.

It is recommended for use in commercial transport application only, where a higher than normal amount of impact is expected.

PRODUCTS


Paraglaze Basecoat Colour	PM-BMIX
Paraglaze CT Basecoat Activator	PH-2400
Paraglaze Reducer Low Temp	PS-6100
Paraglaze Reducer Standard	PS-6200
Paraglaze Reducer High Temp	PS-6300

SUBSTRATES & PREPARATION



All suitably prepared and primed substrates, as recommended in the Paraglaze Basecoat Colour (PM-BMIX) Technical Data Sheet.

MIXING RATIO BY VOLUME



PRODUCT	PARTS
PM-BMIX	1
PH-2400	10%
Paraglaze Reducer	1

Add PH-2400 to PM-BMIX first and thoroughly mix → Then add Paraglaze Reducer.

RECOMMENDATIONS

Paraglaze CT Basecoat Activator may be added to Paraglaze Basecoat ONLY.

Refer to Paraglaze Basecoat Colour (PM-BMIX) Technical Data Sheet for complete technical and application information.

EQUIPMENT CLEANING

After use, clean all equipment thoroughly with cleaning solvent or thinner.

HEALTH AND SAFETY

Refer to Safety Data Sheets (SDS) for full Health and Safety details, as well as product can labels.

Protec hardeners and activated products contain isocyanate and therefore particular safety precautions must be taken; please refer to SDS for full health and safety details.

This product is for professional use only.
The information given in this sheet is for guidance only. Any person using the product without first making further inquiries as to the suitability of the product for the intended purpose does so at his or her own risk and we can accept no liability for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.
Drying times quoted are average times at 25°C/77°F. Film thickness, humidity and shop temperature can all affect drying times.

**Protec Pty Ltd. 97–105 Bedford Street
Gillman, S.A. 5013 Australia**

EMERGENCY RESPONSE NUMBER, Australia: 1800 883 254

**Protec Pty Ltd. 5 Monahan Rd, Mt Wellington
Auckland, New Zealand**

EMERGENCY RESPONSE NUMBER, New Zealand: 0800 000 096

Protec and the *Protec Logo* are registered trademarks of Protec Pty Ltd.